



01-20

 **MOJO**®

Made in Germany

KART RACING TYRE

MOJO D2 XX* | D2-6

D2 XX* rear: 7.1 / 11.0 - 5 | front: 4.5 / 10.0 - 5

D2-6 rear: 6.0 / 11.0 - 5 | front: 4.5 / 10.0 - 5

0,65 (± 0,05) bar

9,43 (± 0,73) psi

recommended pressures (cold)

***CIK-FIA homologated** 

SAFETY WARNING:

- FOR RACING PURPOSE ONLY!
- Max. speed: 180 km/h (112 mph)
- Inflate tyres using a safety cage
(Inflation pressure must not exceed 4,0 bar/58 psi).
- Always mount tyre on specified rim only.
- Never use cracked, rusted or deformed rims.
- Use lubricant (tyre paste) when mounting tyre on rim.
- Mount tyres with correct direction of rotation.
- Do not use screwdrivers etc. to mount tyre onto rim.
- Beware the bead locking screws are not protruding through the rim when inflating the tyre.
- Do not store tyres below -10°C (14°F).
- When fitting tyres on rims and initial inflation, tyre temperature must be above +15°C/60°F.
- The use of tyre softeners or tyre treatments of any kind is prohibited.

For more information please visit:

www.rotax-racing.com

www.mojo-tyres.com